

DAHLGREN DIVISION  
NAVAL SURFACE WARFARE CENTER  
Dahlgren, Virginia 22448-5100



NSWCDD/MP-94/365

INFRARED REFRACTION AND MIRAGES


BY BILL TRAHAN  
SHIP DEFENSE SYSTEMS DEPARTMENT

JANUARY 1995


Approved for public release; distribution is unlimited.

DTIC QUALITY INSPECTED 6

19950815 011



# DISCLAIMER NOTICE



THIS DOCUMENT IS BEST QUALITY AVAILABLE. THE COPY FURNISHED TO DTIC CONTAINED A SIGNIFICANT NUMBER OF COLOR PAGES WHICH DO NOT REPRODUCE LEGIBLY ON BLACK AND WHITE MICROFICHE.

## FOREWORD

Mirages and other atmospheric refraction effects were observed and measured in the mid-wave infrared band (3 to 5  $\mu\text{m}$ ) during a recent field test. High-resolution recorded imagery is presented, including inferior and superior mirages. The affect of a superior mirage on target reporting by an infrared search and track simulation system is shown. This work is part of a continuing program to correlate IR refraction effects with simultaneous radio frequency propagation effects.

The following members of the horizon infrared surveillance sensor (HISS) and infrared propagation (IRP) test are acknowledged for their help in supplying data for this report between February and April 1994. The members of the HISS Test Team were Pat Dezeuw (team leader), Everett Bryant, Robert Headley, Ken Hepfer, Connie Huffman, Keith Merranko, and Sheldon Zimmerman. The members of the IRP Test Team were Barry Henderson, Homar Rivera and Bill Trahan.


This report has been reviewed by Roger Carr, Head, Electro-Optical Systems Branch and Stuart Koch, Acting Head, Search and Track Division.

Approved by:



T. C. PENDERGRAFT, Head  
Ship Defense Systems Department

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution/	
Availability Codes	
Avail and/or	Special
A-1	



Hello, my name is Bill Trahan. Today, I am going to discuss infrared refraction in the atmosphere and the formation of mirages. I will provide some measurements of infrared refraction, recorded during a recent field test, as well as images of mirages in the infrared.

NSWCDD/MP-94/365


# Infrared Refraction and Mirages



Wallops Island, Feb - Apr, '94

Bill Trahan  
Electro-Optical Systems Branch, F44  
Naval Surface Warfare Center, Dahlgren Division

Refraction is the bending of light rays caused by changes in the propagation medium. In the atmosphere, the index of refraction at visible and infrared wavelengths varies with its density. Temperature, humidity, and pressure are the primary factors determining the density of the air. Near the Earth's surface, it is the vertical profile of air temperature, known as the lapse rate, that is the most important factor in determining infrared (and visible) refraction. Mirages are formed when atmospheric refraction begins to focus the light much as a lens would.



- Refraction is the bending of light rays as they pass obliquely through mediums with differing indexes of refraction.
- Changes in atmospheric density cause variations to the index of refraction. Although the variations are small, the long path lengths make the effect measurable.



Through the next few viewgraphs, the effect of different atmospheric conditions upon refraction will be contrasted.

First, as a baseline, neutral conditions are presented. These conditions occur when the air temperature does not change as a function of height. The concern here is with only the lowest 40 or so meters of the atmosphere.

Since the air temperature profile is difficult to measure directly, the air-sea temperature difference (ASTD) is the gauge most often used to indicate the atmospheric condition. The air temperature is measured at a height of 2 to 6 m. This height is not critical as most of the change occurs in the first meter above the water. Since the atmosphere is in thermal contact with the sea surface, the water temperature is assumed to equal the lowest atmospheric temperature.



■ Jargon:

- Air-Sea Temperature Difference (ASTD)
- Atmospheric Condition
- Refractive Condition

Zero  
Neutral  
Nominal

■ Effects:

- Convection
- Dip Angle
- Horizon Range
- Scintillation
- Model Predictions

Some  
Normal  
Normal  
Normal  
Fair


How the different atmospheric conditions affect the appearance of an image, using ray traces, is also shown.

The index of refraction as a function of height is modeled from a given set of meteorological data. With that, rays at various elevation angles are traced from the observer back to the source of the radiation. Along the rays that stop at the sea surface, the observer would see the water. Along those that proceed out of the top of the graph, the observer sees sky. The lowest ray that just skims the sea surface indicates the elevation angle of the horizon. The region of space to the right of the bundle of rays is beyond and below the horizon from the observer's perspective. The only way in which the observer can increase the maximum range to a target is to move to a higher altitude.


In the picture, a boat has been fixed at the same range as the horizon, approximately 8.5 nmi, in this case.



■ Ray Trace:



■ Appearance:



When the air becomes colder than the water, the atmosphere becomes unstable. The air next to the sea surface is warmed by the water and convection increases. This mixing of the air vertically, along with the wind moving the air horizontally, creates a horizontally uniform lapse rate. Atmospheric models are most accurate under these conditions.

Under unstable conditions, the range to the horizon is shorter than for neutral conditions. The horizon is also at a lower elevation. A mirage, known as the inferior mirage, often forms under these conditions. It is the inferior mirage that is seen on distant road surfaces on sunny days. It is called inferior because the mirage image forms below the original image.



■ Jargon:

- Air-Sea Temperature Difference (ASTD)
- Atmospheric Condition
- Refractive Condition

Negative  
Unstable  
Sub-refractive

■ Effects:

- Convection
- Dip Angle
- Horizon Range
- Scintillation
- Model Predictions
- Mirage Type, Frequency


Much  
Increased  
Decreased  
Increased  
Good  
Inferior, Common

The ray trace is generated from that same set of meteorological data as before, except the air temperature is now two degrees cooler. The region on the right where the lower rays cross those above is called the mirage zone. An object in this zone is seen at two different elevation angles by the observer. The range to the horizon is now about 6.5 nmi. Again, only increasing the observer's height can increase the acquisition range to a low flying target.


In the picture, the boat is still held at 8.5 nmi. The lower hull is now obscured by the inferior mirage, which appears as an inverted image. The horizon is at a lower elevation than before.



▪ Ray Trace:



▪ Appearance:





Stable conditions occur when the air temperature is warmer than the water temperature. This kind of profile discourages convection, reducing the mixing of the atmosphere. The atmosphere can even become stratified. Refraction models perform poorly under these conditions, since a stratified profile cannot be determined from only two temperature measurements.

Stable conditions produce an increased range to the horizon, and the elevation of the horizon is increased. A different type of mirage can be seen under these conditions, the superior mirage. The formation of a superior mirage depends upon the presence of a temperature inversion in the atmosphere, a layer of air warmer than that below. In a superior mirage, additional images appear above the original image. A single temperature inversion can create two additional images. However, the formation of this type of mirage can be quite complex.



■ Jargon:

- Air-Sea Temperature Difference (ASTD)
- Atmospheric Condition
- Refractive Condition

Positive  
Stable  
Super-refractive

■ Effects:

- Convection
- Dip Angle
- Horizon Range
- Scintillation
- Model Predictions
- Mirage Type, Frequency


Little  
Decreased  
Increased  
Increased  
Poor  
Superior, Uncommon

The meteorological conditions used to generate this stable condition are identical to the previous cases, except the air temperature is now two degrees warmer than the water. The ray trace shows one of the problems with the refraction models. The temperature profile continues to increase with height. The rays of increasing elevation are bent back toward the Earth's surface, encountering it at increasing range. In the real atmosphere, there is height at which the air will begin to cool with increasing altitude. At that point, the rays will no longer bend towards the Earth, but away from it. Current atmospheric models do not predict the height at which this will occur.


The picture shows how objects in the field of view, such as the boat, are now at a higher apparent elevation. The horizon is both at a high elevation and now farther than the boat. Since the maximum range to a target is attenuation limited, the observer does not get a range increase by increasing the height.



▪ Ray Trace:



▪ Appearance:




Conditions for this picture are the same as before, except that a temperature inversion has been added. At a level above the observer, the index of refraction was changed to show a higher than predicted air temperature. Rays passing into this stratum are bent down more strongly than those below.


As the elevation angle increases, the range to the source of the rays is increasing until about 22 nmi. At that point, the rays are being bent by the temperature inversion and the ranges actually decrease, for increasing observer elevation, to about 20 nmi. Thereafter, the ranges increase with increasing elevation. If the boat is placed at about 21 nmi, it would appear as shown. The rays sweep over that point three times producing the three images of the boat.



▪ Ray Trace:



▪ Appearance:



Parts of a recent field test, at Wallops Island, Virginia, were devoted to the measurement of infrared refraction effects.

Heaters were mounted at fixed heights on the bow and stern of a boat. As the boat moved radially with respect to the sensor, the maximum possible range to the target could be measured.

A similar heater was mounted on a tower located at Parramore Island, about 16.2 nmi south-southwest from Wallops Island. The height of this heater could be set anywhere from 14.33 to 87.33 ft above mean sea level. Thus, for a fixed range, the refraction effects at various heights could be measured.

Other targets [an outbound Lear jet, and an inbound TLX-1] provided qualitative information of the atmosphere. The TLX-1 was a target towed by a Lear jet, which could be made to provide a infrared target.




## Targets

- 20 W/Ster heater mounted on "Sealion"
- 20 W/Ster heater mounted at Parramore Island
- Lear jet
- TLX

## Scenarios

- "Sealion"
  - Fixed heater height
  - Radially inbound or outbound motion
- Parramore Is.
  - Fixed heater range
  - Vertical motion on tower
- Lear jet
  - Low altitude, radially outbound flight
- TLX
  - Low altitude, radially inbound flight





There were two infrared sensors at the field test. The HISS is a research infrared search and track system. While not devoted to the propagation task, many of its measurements are applicable. The IRP sensor was actually part of a larger experiment to correlate propagation effects between the infrared and radio frequency bands.



■ HISS Sensor

- 3.8 - 4.2  $\mu\text{m}$  spectral band
- 256 x 256 focal plane array
- HgCdTe detectors
- 80 x 80  $\mu\text{rad}$  instantaneous field of view
- 80 x 80  $\mu\text{rad}$  spot size
- 1.17v x 15h degree field of regard
- Noise equivalent irradiance of 2e-14 W/cm<sup>2</sup>-ster
- 1 sec scan update rate

■ IRP Sensor



- 3.9 - 5.1  $\mu\text{m}$  spectral band
- 256 x 256 focal plane array
- InSb detectors
- 33 x 33  $\mu\text{rad}$  instantaneous field of view
- 60 x 60  $\mu\text{rad}$  spot size
- 0.48 x 0.48 degree field of view
- Noise equivalent irradiance of 3e-14 W/cm<sup>2</sup>-ster
- staring

This photograph shows the setup of the HISS and IRP sensors on the roof of Building Z-41 at Wallops Island.

The HISS sensor is on the platform in the right of the picture. The height of its optical axis is 25.38 m above mean sea level.

The IRP sensor inside the wooden box is near the center of the picture. It is 22.03 m above mean sea level.

From this perspective, the Atlantic Ocean is behind the photographer.



IRP sensor


HISS sensor

These are the maximum possible acquisition ranges that were measured in the HISS (PHASE I) field test. The predictions came from a formula developed by, the Defence Research Establishment (DREV), Valcartier, Quebec, Canada.

The data shows that refraction is a major factor in acquisition range.




# Maximum Intervisibility Range (MIVR) [Nmi]




This graph shows the maximum possible acquisition ranges to the heaters carried by *Sealion*, during the latest field test. The predictions are again from the DREV formula.

The poor performance on the day with the +3.4 °C ASTD was due to poor atmospheric transmission conditions, and not a refraction effect. Both field tests indicate that the behavior is well behaved for negative ASTD, and more variable for positive ASTD.




Maximum Intervisibility Range (MIVR) [Nmi]






This viewgraph shows an example of an observed inferior mirage. March 11 was a day of unstable atmospheric conditions. The air temperature was at 1.7 °C, the water temperature 4.7 °C, for an ASTD of -3.0 °C. As the *Sealion* moved radially outbound, an inferior mirage of the target formed at the horizon, at 8.5 nmi. The two images eventually merged to one, which disappeared above the horizon at 10 nmi.



0.48 deg

"Sealion" at 8.4 nmi.




0.48 deg

"Sealion" at 10 nmi.


0.18 deg

These images show the inferior mirage of the heater on Parramore Island, also on 11 March. In this case, as the heater moves to a lower height, the two images merge and disappear when the heater moves below 66 ft.



0.48 deg

Heater at 84ft



0.48 deg

Heater at 66ft


0.18 deg

March 1 was a day of unstable conditions. The air temperature was 2.6 °C and the water temperature was 3.7 °C for an ASTD of -1.1 °C. The observed test involved the *Sealion* making runs to the horizon when the Lear jet, which was involved in another test at the time, crossed into the field of view.

The sequence of pictures show the outbound Lear Jet entering the mirage zone. At that point, a second, inferior (lower) image of the Lear appears at the horizon. As the plane continues outbound, the two images coverage into a single image, which disappears above the horizon. Given the speed of the plane, the process took only a couple of seconds.

The *Sealion*, in the first picture is already closer than the range to the mirage zone.

NSWCDD/MP-94/365




"Sealion" @ 10nmi    Lear jet @ 30nmi, 560ft

0.48 deg



060:19:21:00



060:19:21:01




0.38 deg

This viewgraph shows a rapid change in the elevation of the horizon in progress, seen on 23 March. The contrast of the pictures has been greatly enhanced to compensate for the loss in the printing process. The four images present a panorama of the sea. The horizon on the right is at a higher elevation than the horizon on the left. *Streamers* are rising up from the original horizon, moving from right to left, and filling in the space to the new horizon. In a matter of minutes, the effect moved across the field of view presented until no trace of the original horizon remained.

The effect points out a weakness of current refraction modeling. A set of temperature measurements at a single location cannot be adequate to cope with an effect that can be so spatially and temporally dependent.




082:14:16:01





On 23 March, a superior mirage was observed. In the first picture, the *Sealion*, at 16.6 nmi, is already beyond the typical range to the horizon. Soon thereafter, two to three images of the target appear. As the range increased, the target became a single image again, at a noticeable higher elevation than before.



0.38 deg

0.48 deg

"Sealion" at 16.6nmi



082:16:25:12




082:16:25:33




082:16:26:13

"Sealion" at 17.5nmi

This viewgraph shows the dramatic increase in the elevation angle to the horizon that is possible under stable atmospheric conditions. Under most conditions, the *Sealion* at 12 nmi would be near the horizon. On this day, 24 March, a superior mirage has created a wall of water extending nearly 4 mrad above the "Sealion". Soon thereafter, the image of the *Sealion* faded from view, before it *climbed the wall* as in the previous day,



On 18 February, the *Sealion* made two outbound and two inbound runs to the horizon. During the first outbound run there was no mirage, only an increased range to the horizon. In the first inbound run, a small superior mirage formed for a short time. By the time of the second inbound run, shown in the picture, the superior mirage had become spectacular with multiple images of the target appearing and disappearing. The dark band, an image of the sea, would sometimes grow, sometimes disappear, with the horizon elevation changing as well.




0.38 deg

0.48 deg

"Sealion" at 17.7 Nmi

This is another view of the superior mirages witnessed on 24 March. In this case, it is multiple images of the heater at Parramore Island.



Multiple images of heater  
at 84 ft (083:15:47:31)

Apparent Horizon Elevation


Elevation Of Horizon  
Under Neutral Conditions



This is a superior mirage to the TLX target, on 24 March. When the target was first acquired, it appeared very blurred and distorted. As the range decreased, the image started to stretch vertically. A second image of the target emerged from the top of the field of view and merged with the first into a single image that faded from view. However, a fade zone cannot be inferred since the HISS began detecting the target at this point; another image of the target was above our field of view.



13.5nmi



TLX

0.48 deg

083:15:19:55

11.8nmi



10.1nmi





8.7nmi



0.38 deg

083:15:20:19 083:15:20:56 083:15:21:01

This viewgraph shows detections on an outbound Lear jet by the HISS sensor on 24 March. The detections and pictures of the target depict the formation of multiple images by a mirage. The gap in detections between 100 and 125 sec seems to be caused by a fade zone in which no energy was received from the target. However, in the gap occurring after 160 sec, the lowest image of the target remained in the video, though was too faint to exceed the HISS detection threshold.



The outbound Lear jet was a difficult target for the IRP sensor to acquire and track, due to the very small field of view and awkward azimuth control. However, on 24 March, the effort produced a spectacular image of a superior mirage. (This is a different run than the HISS detections shown in the previous viewgraph.) The plane was acquired as two images that were below the horizon. The two images merged into one and disappeared for nearly 3 sec. The jet then reappeared as a single image at the horizon and, thereafter, increased in elevation.




17.6nmi

18.2nmi

Apparent  
Horizon

Nominal  
Horizon



083:20:58:10

083:20:58:11

083:20:58:12 083:20:58:15

083:20:58:17

0.068 deg

0.38 deg

Refraction observations were made on 29 days during the test period. On 14 days, we observed stable conditions; on 11 days, unstable conditions. Since neutral conditions are really a transition state, the four days that remained near neutral during our observations were arbitrarily listed as neutral.

Superior mirages were observed on six of the days with stable conditions. All 11 days of unstable conditions exhibited inferior mirages.

On two days, the superior mirages were spectacular and produced "fade zones". These were regions in which the target was not visible, but would reappear at longer ranges. On 18 February, the "Sealion" passed through two small fade zones on one outbound run. Then, on 24 March, Fade zones were observed in the outbound flights of the Lear jet. However, there were no fade zones observed during the "Sealion" runs on this day.



Met. Condition	Mirages	Fade Zones
Stable (Positive ASTD) 14 days	Superior 6 days	2 days
Neutral 4 days		
Unstable (Negative ASTD) 11 days	Inferior 11 days	



This field test proved many opportunities to observe different atmospheric conditions. This presentation illustrated the most spectacular mirages witnessed on five of the days. Several conclusions can be drawn from these observations.

Refraction effects are common and as changeable as the weather. In unstable atmospheric conditions, refraction is easily predicted from the air and sea temperature measurements. To accurately predict refraction effects in stable atmospheric conditions may require detailed temperature profiles at several points along the optical path.

The same conditions that produce mirages in the visible will produce infrared mirages. Inferior mirages are well behaved, but superior mirages are more difficult to predict. Superior mirages are sometimes associated with *fade zones* in which the target signature is greatly diminished. However, mirages are a long-range effect, and are usually short lived upon a radially moving target.



- IR refraction effects are common and are an important factor in the long range acquisition and tracking of a low altitude target.
- As weather conditions change, so to do refraction effects.
- The ability to predict refraction effects requires sufficient met collection.
- Atmospheric conditions that cause mirages in the visible band do so in the infrared as well.
  - Inferior mirages are common, with predictable effects.
  - Superior mirages are less common, with effects that are more difficult to predict.
  - IR "fade zones" are sometimes associated with superior mirages.
  - Mirages are dependent upon the target's range and height. It is a long range and, for a radially moving target, transient phenomenon.

# DISTRIBUTION

	Copies		Copies
DOD ACTIVITIES (CONUS)		ATTN CAPT WILSON USAF	1
ATTN CODE 723 (OSTROWSKI)	1	OFFICER IN CHARGE	
COMMANDER		JOINT ELECTRONIC WARFARE CENTER	
CARDEROCK DIVISION		2 HALL BLVD STE 217	
NAVAL SURFACE WARFARE CENTER		SAN ANTONIO TX 78243-7008	
SHIP IR SIGNATURES AND COUNTERMEASURES			
BETHESDA MD 20084-5000		ATTN CODE 501B (CAMPANA)	1
		NAVAL AIR DEVELOPMENT CENTER	
ATTN OPNAV N865D (CDR JENKINS)	1	WARMINSTER PA 18974-5000	
OPNAV N865D1 (CDR MACY)	1		
CHIEF OF NAVAL OPERATIONS		ATTN CONWAY	1
WASHINGTON DC 20350-2000		JONES	1
		SMITH	1
ATTN CODE 805 (BENNETT)	1	COMMANDING OFFICER	
COMMANDER		NAVAL AIR WARFARE CENTER	
CRANE DIVISION		AIRCRAFT DIVISION LAKEHURST	
NAVAL SURFACE WARFARE CENTER		LAKEHURST NJ 08733-5000	
300 HIGHWAY 361			
CRANE IN 47522-5001		ATTN COLBY	1
		COMMANDER	
ATTN CODE E29L (TECHNICAL LIBRARY)	1	NAVAL AIR WARFARE CENTER	
COMMANDING OFFICER		AIRCRAFT DIVISION	
CSSDD NSWC		BLDG 304	
6703 W HIGHWAY 98		PATUXENT RIVER MD 20670-5304	
PANAMA CITY FL 32407-7001			
		ATTN ADAMYCK	1
DEFENSE TECHNICAL INFORMATION CENTER		COMMANDER	
CAMERON STATION		NAVAL AIR WARFARE CENTER	
ALEXANDRIA VA 22304-6145	12	WEAPONS DIVISION	
		521 9TH ST	
		POINT MUGU CA 93042-5001	

## DISTRIBUTION (Continued)

	Copies		Copies
ATTN CODE 5622 (PRIEST)	1	ATTN ONR 31 (BUSS)	1
CODE 5622 (SHETTLE)	1	ONR 31 (HALL)	1
CODE 5622 (TAKKEN)	1	COMMANDER	
COMMANDING OFFICER		OFFICE OF NAVAL RESEARCH	
NAVAL RESEARCH LABORATORY		800 N QUINCY STREET	
4555 OVERLOOK AVENUE SW		ARLINGTON VA 22217-5660	
WASHINGTON DC 20375-5320			
ATTN PMS 400B30A (CDR WILSON)	1	ATTN CODE P2333 (SHELTON)	1
SEA 62Y	1	PACIFIC MISSILE TEST CENTER	
SEA 91W21 (READING)	1	POINT MUGU CA 93042-5000	
COMMANDER		ATTN ANDERSON	1
NAVAL SEA SYSTEMS COMMAND		KNEIZYS	1
2531 JEFFERSON DAVIS HWY		PHILLIPS LABORATORY AFSC OPS	
ARLINGTON VA 22242-5160		HANSCOM AIR FORCE BASE MA 01731-5000	
ATTN CODE 764 (FORBES)	1	ATTN PEO TAD D2 (CAPT WILLIAMSON)	1
CODE 764 (METCALF)	1	PEO TAD D233 (LAM)	1
COMMANDING OFFICER		PEO TAD D233 (MISANIN)	1
NCCOSC RDTE DIV 754		PROGRAM EXECUTIVE OFFICER	
49336 DIGITAL ROAD		THEATER AIR DEFENSE	
SAN DIEGO CVA 92152-7620		2531 JEFFERSON DAVIS HIGHWAY	
ATTN BUSER	1	ARLINGTON VA 22242-5170	
SELF	1	ATTN CODE 4Y21 (ECK)	1
NIGHT VISION AND ELECTRONIC SENSORS		COMMANDER	
DIRECTORATE		PORT HUENEME DIVISION	
10221 BURBECK ROAD		NAVAL SURFACE WARFARE CENTER	
FORT BELVOIR VA 22060		4373 MISSILE WAY	
		PORT HUENEME CA 93043-4307	

DISTRIBUTION (Continued)

	Copies		Copies
ATTN SPAWAR 332 (GIRATA) COMMANDER SPACE AND NAVAL WARFARE SYSTEMS COMMAND 2451 CRYSTAL RD ARLINGTON VA 22445-5200	1	ATTN SMITH DIBIASIO AMBER 5756 THORNWOOD DRIVE GOLETA CA 93117-3802	1 1
ATTN LT SLOOP COMMANDING OFFICER SURFACE WARFARE DEVELOPMENT GROUP NAVAL AMPHIBIOUS BASE LITTLE CREEK NORFOLK VA 23521-5160	1	ATTN PROVENCHER ANDREW KINTEC INC 2908 NATIONAL DRIVE GARLAND TX 75041	1
ATTN LANICH WRIGHT PATTERSON AIR FORCE BASE WRDC AARI 1 WRIGHT PATTERSON AIR FORCE BASE OH 45433-6543	1	ATTN DAVIS LUBARD ARETE P O BOX 6024 SHERMAN OAKS CA 91413	1 1
NON-DOD ACTIVITIES (CONUS)		ATTN HAMM BALL AEROSPACE SYSTEM DIVISION P O BOX 1062 BOULDER CO 80306	1
ATTN WHITE ABA ELECTROMECHANICAL SYSTEMS INC P O BOX 500 PINELLAS PARK FL 34290-0500	1	ATTN AX BDM FEDERAL INC 4001 NORTH FAIRFAX DRIVE SUITE 750 ARLINGTON VA 22203	1
ATTN DR SCOTT AERODYNE RESEARCH INC 45 MANNING ROAD BILLERICA MA 01821-3976	1	ATTN ROY BOEING DEFENSE AND SPACE GROUP 1700 NORTH MOORE STREET ROSSLYN VA 22209-1989	1

DISTRIBUTION (Continued)

	Copies		Copies
ATTN GRIMM	1	ATTN BAUR	1
THE CNA CORPORATION		PINES	1
P O BOX 16268		REY	1
ALEXANDRIA VA 22302-0268			
		HUGHES	
ATTN ARMINTROUT	1	ELECTRO OPTICAL SYSTEMS	
MALONE	1	LOC EO BLDG E1 MS A151	
CONTRAVES		2000 EAST EL SEGUNDO BOULEVARD	
615 EPSILON DRIVE		P O BOX 902	
PITTSBURGH PA 15238-2880		EL SEGUNDO CA 90245	
ATTN MCNALLY	1	ATTN MILLER	1
DBA SYSTEMS INC		IN DEF SERVICES INTERNATIONAL	
BELTWAY BUILDING SUITE 200		2735 HARTLAND ROAD SUITE 300	
9301 ANNAPOLIS ROAD		FALLS CHURCH VA 22043	
LANHAM SEABROOK MD 20706			
		ATTN BIBERMAN	1
FAIRCHILD WESTON SYSTEMS INC		DALCHER	1
IMAGING SYSTEMS DIVISION		FRIDLING	1
300 ROBBINS LANE		NICHOLL	1
SYOSSET NY 11791	1	INSTITUTE OF DEFENSE ANALYSIS	
		1801 N BEAUREGARD	
ATTN ZIMMERMAN	1	ALEXANDRIA VA 22311	
HONEYWELL			
AEROSPACE AND DEFENSE GROUP		ATTN FIGURSKI	1
7900 WESTPARK DRIVE		THE IRIA CENTER	
McLEAN VA 22102		ERIM	
		P O BOX 134001	
		ANN ARBOR MI 48113-4001	

## DISTRIBUTION (Continued)

	Copies		Copies
ATTN DOCKERY	1	ATTN DUGANNE	1
LEWIS	1	MCDONNELI DOUGLAS ELECTRONIC SYSTEMS	
PERI	1	700 ROYAL OAKS DRIVE	
PRENGAMAN	1	P O BOX 5005	
REILLY	1	MONROVIA CA 91017-7105	
JOHNS HOPKINS UNIVERSITY			
APPLIED PHYSICS LABORATORY		ATTN: HUYGEN	1
JOHNS HOPKINS ROAD		MAGNAVOX SIGNAL SYSTEMS COMPANY	
LAUREL MD 20723-6099		215 KEYSTONE ROAD	
		MONTGOMERYVILLE PA 18936	
ATTN JONES	1		
KOLLMORGEN CORPORATION		ATTN B MURTHA	1
ELECTO OPTICAL DIVISION		MARTIN MARIETTA ELECTRONICS AND MISSILES	
347 KING STREET		P O BOX 55837 MP 718	
NORTHAMPTON MA 01060-2390		ORLANDO FL 32855-5837	
ATTN GIFT AND EXCHANGE DIVISION		ATTN BROWN	1
LIBRARY OF CONGRESS		GAUBLE	1
WASHINGTON DC 20540	4	VON LINTAG	1
		MARTIN MARIETTA	
ATTN MOORE	1	GOVERNMENT ELECTRONIC SYSTEMS	
LOCKHEED SANDERS INC		199 BORTON LANDING ROAD	
MER15 1204		P O BOX 1027	
P O BOX 868		MOORESTOWN NJ 08057-0927	
NASHUA NH 03061-0868			
		ATTN CANTELLA	1
ATTN CARR	1	OTAZO	1
KOLP	1	MASSACHUSETTS INSTITUTE OF TECHNOLOGY	
MORRISON	1	LINCOLN LABS	
LORAL DEFENSE SYSTEMS AKRON		244 WOOD STREET	
1210 MASSILLON ROAD		LEXINGTON MA 02173	
AKRON OH 44315-0001			

## DISTRIBUTION (Continued)

	Copies		Copies
ATTN DARREN MITRE CORPORATION 5254 POTOMAC DRIVE SUITE 5 DAHLGREN VA 22448	1	ATTN FOWKS KWOK ROCKWELL INTERNATIONAL CORPORATION TACTICAL SYSTEMS DIVISION 3370 MIRALOMA AVENUE P O BOX 4921 ANAHEIM CA 92803-4921	1
ATTN BRAY NORTHUP ELECTRO MECHANICAL DIVISION 500 EAST ORANGETHORPE AVENUE ANAHEIM CA 92801	1	ATTN DR BERK DR GRUNINGER SPECTRAL SCIENCES INC 99 SOUTH BEDFORD STREET BURLINGTON MA 01803	1 1
ATTN SCHROEDER ONTAR CORPORATION 9 VILLAGE WAY NORTH ANDOVER MA 01845	1	SPERRY CORPORATION AEROSPACE AND MARINE GROUP CHARLOTTESVILLE VA 22906	1
ATTN SCHAFFER PILKINGTON OPTRONICS INC 7550 CHAPMAN AVENUE GARDEN GROVE CA 92641	1	ATTN VAN DER SCHOEFF STRATEGIC INSIGHT 2011 CRYSTAL DRIVE SUITE 101 ARLINGTON VA 22202	1
ATTN LAFFAN QUESTECH INC 7600 A LEESBURG PIKE FALLS CHURCH VA 22043	1	ATTN GUNSALLUS SIMMONS TEXAS INSTRUMENTS DEFENSE SYSTEMS AND ELECTRONICS GROUP 8505 FOREST LANE P O BOX 660246 MS 3150 DALLAS TX 75246	1 1
ATTN GOLDMAN LAMBERT RAYTHEON COMPANY MISSILE SYSTEMS DIVISION 50 APPLE HILL DRIVE TEWKSBURY MA 01876-0901	1 1		



## DISTRIBUTION (Continued)

	Copies		Copies
ATTN KIM TRW DEFENSE SYSTEMS GROUP 7600 COLSHIRE DRIVE McLEAN VA 22102	1	NON-DOD ACTIVITIES (NON-CONUS)	
ATTN OTTERSON WESTINGHOUSE ELECTRIC CORPORATION P O BOX 1488 MS 9815 ANNAPOLIS MD 21404	1	ATTN CHEVRETTE SMITHSON DEFENCE RESEARCH ESTABLISHMENT VALCARTIER ELECTRO OPTICS DIVISION P O BOX 8800 COURCELETTE PQ G0A 1R0 CANADA	1 1
ATTN WEYGANDT WESTINGHOUSE ELECTRIC CORPORATION ELECTRONIC SYSTEMS GROUP P O BOX 746 MS G8 BALTIMORE MD 21203	1	ATTN DR WOODRUFF DEFENCE SCIENCE AND TECHNOLOGY OFFICE LAND SPACE AND OPTOELECTRONICS DIVISION P O BOX 1500 SALISBURY SOUTH AUSTRALIA 5108	1
ATTN ARKIN WESTINGHOUSE ELECTRO OPTICAL SYSTEMS ORLANDO 9820 SATELLITE BOULEVARD ORLANDO FL 32821	1	ATTN FAO (LCDR LOVELOCK) DGSW(N) DRA PORTSDOWN PORTSMOUTH ENGLAND	1
ATTN SHIPMAN XYBION CORPORATION 240 CEDAR KNOLLS ROAD CEDAR KNOLLS NJ 07927-1698	1	ATTN CAPT (RES) HARPASI ELBIT LTD ADVANCED TECHNOLOGY CENTER P O BOX 539 HAIFA 31053 ISRAEL	1
		ATTN ANDRESSEN ELECTRO OPTICS INDUSTRIES LTD OPTRONICS SYSTEMS DIVISION P O BOX 1165 REHOVOT 76111 ISRAEL	1

## DISTRIBUTION (Continued)

	Copies		Copies
ATTN HUTCHINGS	1	ATTN EDWARDS	1
KNEPPER	1	PARADIGM PATHWAYS GROUP	
HOLLANDSE SIGNAALAPPARATEN		26 BEATTY CRESCENT	
P O BOX 42		AURORA ON L4G 5V1 CANADA	
7550 GD HENGELLO THE NETHERLANDS			
ATTN DENIS KERANFORN	1	ATTN MCQUOID	1
MINISTERE DE LA DEFENSE		PILKINGTON PE LTD	
DIRECTION DES CONSTRUCTIONS ET ARMES NAVALES		GLASCOED ROAD	
8 BOULEVARD VICTOR		ST ASAPH CLWYD WALES LL17 0LL	
75 732 PARIS CEDEX 15 FRANCE			
ATTN HUMMEL	1	ATTN SEGAL	1
MINISTRY OF DEFENCE		RAFAEL	
DMKM WCS		P O BOX 2250 (4A)	
HEMDC		HAIFA 31053 ISRAEL	
VD BURCHLAAN 31		ATTN SAMUELSSON	1
POSTBUS 20702		SAAB MISSILES AB	
2500 ES DEN HAGG THE NETHERLANDS		P O BOX 13045	
		S 402 51 GOTEBOG SWEDEN	
ATTN DMCS 4 (MULLER)	1	ATTN BOEHM	1
NATIONAL DEFENCE HEADQUARTERS		PICOLLET	1
MARITIME COMBAT SYSTEMS DEPARTMENT		SAGEM	
101 COLONEL BY DRIVE		70 74 RUE DE LA TOUR BILLY	
OTTAWA ON K1A 0K2 CANADA		BP 72	
		95101 ARGENTEUIL CEDEX FRANCE	
ATTN MAI	1		
NAVAL ENGINEERING TEST ESTABLISHMENT		ATTN FEUILLOY	1
161 RUE WANKLYN STREET		MISSIRIAN	1
LASALLE PQ H8R 1Z2 CANADA		SAGEM	
		LE PONANT DE PARIS	
		27 RUE LEBLANC	
		75512 PARIX CEDEX 15 FRANCE	

## DISTRIBUTION (Continued)

	Copies		Copies
ATTN CINELLI	1	E231	3
PIODI	1	E272	1
SAT		F07	1
41 RUE CANTAGREL		F107	1
75631 PARIS CEDEX 13 FRANCE		F11	1
		F21	1
ATTN BROWN	1	F31	1
VAN KEMENADE	1	F32	1
REEVES	1	F32	1
SPAR AEROSPACE LTD		F406	1
ADVANCED TECHNOLOGY SYSTEMS GROUP		F41	1
ELECTRO OPTICAL SYSTEMS DIVISION		F41	1
9445 AIRPORT ROAD		F41	1
BRAMPTON ON L6S 4J3 CANADA		F41	1
		F41	1
ATTN DE JONG	1	F44	1
SCHWERING	1	F44	1
TNO PHYSICS AND ELECTRONICS LABORATORY		F44	1
OUDE WAALSDORPERWEG 63		F44	1
P O BOX 96864		F44	1
2509 JG THE HAGUE THE NETHERLANDS		F44	1
		F44	1
INTERNAL		F44	1
B42 (BARNETT)	1	F44	1
B42 (BILLARD)	1	F44	1
B42 (CROWDER)	1	F44	1
B42 (LEE)	1	F44	1
B42 (PETROPOULOS)	1	G21	1

DISTRIBUTION (Continued)

Copies

G33 (DORAN)  
G42  
G531 (FERSTL)  
G63 (LOW)  
J31  
N24  
N74 (GIDEP)

1  
1  
1  
1  
1  
1  
1  
1

REPORT DOCUMENTATION PAGE			Form Approved OBM No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, search existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE January 1995		3. REPORT TYPE AND DATES COVERED
4. TITLE AND SUBTITLE Infrared Refraction and Mirages			5. FUNDING NUMBERS	
6. AUTHOR(s) Bill Trahan				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Commander Naval Surface Warfare Center, Dahlgren Division (Code F44) 17320 Dahlgren Road Dahlgren, VA 22448-5100			8. PERFORMING ORGANIZATION REPORT NUMBER NSWCDD/MP-94/365	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)			10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) Mirages and other atmospheric refraction effects were observed and measured in the mid-wave infrared band (3 to 5 $\mu$ m) during a recent field test. High-resolution recorded imagery is presented, including inferior and superior mirages. The affect of a superior mirage on target reporting by an infrared search and track simulation system is shown. This work is part of a continuing program to correlate IR refraction effects with simultaneous radio frequency propagation effects.				
14. SUBJECT TERMS Infrared refraction, mirages, HISS, IRST, IRP, DREV, ASTD			15. NUMBER OF PAGES 70	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT	

## **GENERAL INSTRUCTIONS FOR COMPLETING SF 298**

The Report Documentation Page (RDP) is used in announcing and cataloging reports. It is important that this information be consistent with the rest of the report, particularly the cover and its title page. Instructions for filling in each block of the form follow. It is important to ***stay within the lines*** to meet ***optical scanning requirements***

**Block 1. Agency Use Only (Leave blank).**

**Block 2. Report Date.** Full publication date including day, month, and year, if available (e.g. 1 Jan 88). Must cite at least the year.

**Block 3. Type of Report and Dates Covered.** State whether report is interim, final, etc. \*If applicable, enter inclusive report dates (e.g. 10 Jun 87 - 30 Jun 88).

**Block 4. Title and Subtitle.** A title is taken from the part of the report that provides the most meaningful and complete information. When a report is prepared in more than one volume, repeat the primary title, add volume number, and include subtitle for the specific volume. On classified documents enter the title classification in parentheses.

**Block 5. Funding Numbers.** To include contract and grant numbers; may include program element number(s), project number(s), task number(s), and work unit number(s). Use the following labels:

<b>C</b> - Contract	<b>PR</b> - Project
<b>G</b> - Grant	<b>TA</b> - Task
<b>PE</b> - Program Element	<b>WU</b> - Work Unit Accession No.

**Block 6. Author(s).** Name(s) of person(s) responsible for writing the report, performing the research, or credited with the content of the report. If editor or compiler, this should follow the name(s).

**Block 7. Performing Organization Name(s) and address(es).** Self-explanatory.

**Block 8. Performing Organization Report Number.** Enter the unique alphanumeric report number(s) assigned by the organization performing the report.

**Block 9. Sponsoring/Monitoring Agency Name(s) and Address(es).** Self-explanatory.

**Block 10. Sponsoring/Monitoring Agency Report Number. (If Known)**

**Block 11. Supplementary Notes.** Enter information not included elsewhere such as: Prepared in cooperation with...; Trans. of ...; To be published in... . When a report is revised, include a statement whether the new report supersedes or supplements the older report.

**Block 12a. Distribution/Availability Statement.** Denotes public availability or limitations. Cite any availability to the public. Enter additional limitations or special markings in all capitals (e.g. NOFORN, REL, ITAR).

**DOD** - See DoDD 5230.24, "Distribution Statements on Technical Documents"  
**DOE** - See authorities.  
**NASA** - See Handbook NHB 2200.2  
**NTIS** - Leave blank

**Block 12b. Distribution Code.**

**DOD** - Leave blank.  
**DOE** - Enter DOE distribution categories from the Standard Distribution for Unclassified Scientific and Technical Reports.  
**NASA** - Leave blank.  
**NTIS** - Leave blank.

**Block 13. Abstract.** Include a brief (*Maximum 200 words*) factual summary of the most significant information contained in the report.

**Block 14. Subject Terms.** Keywords or phrases identifying major subjects in the report.

**Block 15. Number of Pages.** Enter the total number of pages.

**Block 16. Price Code.** Enter appropriate price code (*NTIS only*).

**Block 17-19. Security Classifications.** Self-explanatory. Enter U.S. Security Classification in accordance with U.S. Security Regulations (i.e., UNCLASSIFIED). If form contains classified information, stamp classification on the top and bottom of this page.

**Block 20. Limitation of Abstract.** This block must be completed to assign a limitation to the abstract. Enter either UL (unlimited or SAR (same as report)). An entry in this block is necessary if the abstract is to limited. If blank, the abstract is assumed to be unlimited.